

THREAD COMPOUND TECHNICAL DATA

NLC-MODIFIED



NLC-Modified was developed as a lead-free API replacement product. This premium quality compound has been extensively tested in laboratory and field operations to assure maximum performance over a wide range of operating conditions. NLC-Modified has been shown to exceed the performance requirements of API Bulletin 5A2 on both premium and conventional tubular connections.

Product Specifications

Service Rating	200° C / 392° F
Drop Point	240° C / 464° F
Brushability	-18° C / 0° F

Service Recommendations

NLC-Modified is recommended for API casing, tubing and line pipe connections

Packaging

10 L Metal	Net 15.9 kg	Shipping 16.8 kg
2.5 US Gal	Net 35.0 lb	Shipping 37.0 lb

Refer to Manufacturer's Material Safety Data Sheet for Precautionary and Handling Information

Calgary OfficeBay 7, 3401 - 19

Phone: 403/219-0255
Fax: 403/291-3042

Clairmont Office 9402 - 99 Street Clairmont, AB TOH 0W0 Phone: 780/567-2398

Fax: 780/567-2413

Red Deer Distribution Centre 7932 Edgar Industrial Way Red Deer, AB T4P 3R2

Phone: 403/341-4417 **Fax**: 403/346-5122

Redcliff Office 114 Elbow Drive N.E. Redcliff, AB TOJ 2P0

Phone: 403/526-3321 Fax: 403/526-8036 **Edmonton Distribution Centre** 9519 - 28 Avenue Edmonton, AB T6N 0A3

Phone: 780/436-3400 Fax: 780/436-3659

Oklahoma City Distribution Centre 8200 West Reno Oklahoma City, OK USA 73127 Phone: 405/491-8521 Fax: 405/491-8521

TOLL FREE: 1-800-222-6449

