

**THREAD COMPOUND TECHNICAL DATA**



# ALLSTAR

Allstar is a premium quality rotary joint compound containing 60% finely powdered metallic lead to absorb shock and protect connections from galling and seizing under high loads. Non-metallic particles are included in the formulation to prevent metal compaction in the shoulder and thread roots ensuring a clean breakout.

**SERVICE RECOMENDATIONS**

**Drill collars at maximum torque in severe drilling conditions**

**PACKAGING**

10 L STEEL      Net 20.4 kg      Net 45 lb

**PRODUCT SPECIFICATIONS**

SPECIFIC GRAVITY      2.41 g/cc  
 SERVICE RATING      240 °C  
 DROPPING POINT      260 °C  
 BRUSHABILITY      -18 °C

Refer to Manufacturer's Material Safety Data Sheet for Precautionary and Handling information.

CALGARY	RED DEER	EDMONTON	CLAIRMONT
Bay 5, 3401 – 19th ST. NE Calgary, Alberta T2E 6S8 Tel.: 403-219-0255 Fax: 403-291-3042	#2, 7920 Edgar Industrial Way Red Deer, Alberta T4P 3R2 Tel.: 403-341-4417 Fax: 403-309-9276	9734 – 47th Avenue Edmonton, Alberta T6E 5P3 Tel.: 780-436-3400 Fax: 780-436-3659	9402 – 99th ST. Clairmont, Alberta T0H 0W0 Tel.: 780-567-2398 Fax: 780-567-2413

