

TOPCO SALES

ECO-SEAL

ECO-SEAL IS AN ECONOMICAL NON-METALLIC COMPOUND FORMULATED FOR USE AS A LUBRICANT AND SEALANT. IT DOES NOT CONTAIN ANY RESTRICTED SUBSTANCES AS DEFINED BY THE CALIFORNIA CODE OF REGULATIONS CONCERNING TOXICS AND HAZARDOUS MATERIALS.

ECO-SEAL IS RECOMMENDED FOR TUBING, CASING AND LINE PIPE CONNECTIONS.



PACKAGING

10 L STEEL
2.5 US GAL
20 L STEEL
5.0 US GAL

NET WEIGHT

9.1 KG
20.0 LB
22.7 KG
50.0 LB

SHIPPING WEIGHT

10.0 KG
22.0 LB
23.6 KG
52.0 LB

PRODUCT SPECIFICATIONS

BASE GREASE CALCIUM/LITHIUM/HECTORITE
COLOUR BLACK
DROPPING POINT 182° C (360° F)

NLGI GRADE 1
PEN RANGE (ASTM D-217) 310 TO 340
BRUSHABLE TO -18° C (0° F)
SERVICE RATING -18° TO 150° C (0° TO 300° F)

**REFER TO MATERIAL SAFETY DATA SHEETS
(AVAILABLE FROM MANUFACTURER) FOR
PRECAUTIONARY AND HANDLING PROCEDURES.**

TOPCO SALES

CALGARY OFFICE

Bay 5, 3401 - 19th Street N.E.
Calgary, Alberta T2E 6S8
Tel.: (403) 219-0255
Fax: (403) 291-3042

EDMONTON

9734 47 Avenue
Edmonton, Alberta T6E 5P3
Tel.: (780) 436-3400
Fax: (780) 436-3659

**TOLL FREE PH. - CANADA: 1-800-222-6448
TOLL FREE FAX - CANADA: 1-888-867-2626**

