

# TOPCO SALES

## MULTI-PAC SILICONE

MULTI-PAC SILICONE IS A HIGH TACK DIELECTRIC COMPOUND WHICH IS HYDROLYTICALLY STABLE AND RESISTANT TO OXIDATION. MULTI-PAC IS WATER REPELLENT AND IS CHEMICALLY INERT. IT HAS GOOD ADHERENCE TO COLD, DAMP SURFACES.

MULTI-PAC IS RECOMMENDED FOR THE SEALING AND ENCAPSULATION OF ELECTRICAL COMPONENTS.



### PACKAGING

### NET WEIGHT

### SHIPPING WEIGHT

TUB

455 GM  
1.0 LB

500 GM  
1.1 LB

CARTRIDGE

455 GM  
1.0 LB

475 GM  
1.04 LB

### PRODUCT SPECIFICATIONS

BASE GREASE	SILICONE
COLOUR	WHITE
DROPPING POINT	232° C (450° F)
DENSITY, TYPICAL	1.01 G/CM <sup>3</sup>
NLGI GRADE	2
PEN RANGE (ASTM D-217)	265 TO 295
BRUSHABLE TO	-18° C (0° F)
SERVICE RATING	-40° TO 204° C (-40° TO 400° F)

**REFER TO MATERIAL SAFETY DATA SHEETS  
(AVAILABLE FROM MANUFACTURER) FOR  
PRECAUTIONARY AND HANDLING PROCEDURES.**



### CALGARY OFFICE

Bay 5, 3401 - 19th Street N.E.  
Calgary, Alberta T2E 6S8  
Tel.: (403) 219-0255  
Fax: (403) 291-3042

### EDMONTON

9734 47 Avenue  
Edmonton, Alberta T6E 5P3  
Tel.: (403) 436-3400  
Fax: (403) 436-3659

**TOLL FREE PH. - CANADA: 1-800-222-6448**  
**TOLL FREE FAX - CANADA: 1-888-867-2626**

