

**THREAD COMPOUND TECHNICAL DATA**



# TK II MODIFIED

TK II is a synthetic based thermal compound developed for use in geo-thermal and steam injection services. This product provides a leak-proof seal in both API and premium connections in high temperatures and pressures. The metallics used in the formulation prevent thread galling and seizure. The chemical inhibitors minimize the effects of corrosive environments.

**SERVICE RECOMENDATIONS**

**Casing and tubing, as well as premium threaded connections**

**PACKAGING**

10 L STEEL      Net 18.4 kg      Net 40 lb

**PRODUCT SPECIFICATIONS**

SPECIFIC GRAVITY      1.92 g/cc  
 SERVICE RATING      370 °C  
 DROPPING POINT      390 °C  
 BRUSHABILITY      -18 °C

Refer to Manufacturer's Material Safety Data Sheet for Precautionary and Handling information.

CALGARY	RED DEER	EDMONTON	CLAIRMONT
Bay 5, 3401 – 19th ST. NE Calgary, Alberta T2E 6S8 Tel.: 403-219-0255 Fax: 403-291-3042	#2, 7920 Edgar Industrial Way Red Deer, Alberta T4P 3R2 Tel.: 403-341-4417 Fax: 403-309-9276	9734 – 47th Avenue Edmonton, Alberta T6E 5P3 Tel.: 780-436-3400 Fax: 780-436-3659	9402 – 99th ST. Clairmont, Alberta T0H 0W0 Tel.: 780-567-2398 Fax: 780-567-2413

