

# MATERIAL SAFETY DATA SHEET

<b>WHMIS HAZARD INDEX: D2A</b> 0 INSIGNIFICANT 1 SLIGHT 2 MODERATE 3 HIGH 4 EXTREME	<b>PRODUCT CODE:</b> FIRE 1 REACTIVITY 0 SPECIAL 0 TOXICITY 1
<b>SECTION 1 LOCATION</b>  TOPCO OILSITE PRODUCTS LTD. BAY 5, 3401 – 19 STREET N.E. CALGARY, ALBERTA CANADA T2E 6S8  PHONE (403) 219-0255 FAX (403) 291-3042	<b>SECTION 6 TOXICOLOGY</b>  <b>ROUTE OF ENTRY:</b> SKIN & EYE CONTACT  <b>CHRONIC EFFECTS:</b> MAY CAUSE IRRITATION AND POSSIBLE DERMATITIS IN SENSITIVE INDIVIDUALS  <b>ACUTE TOXICOLOGY:</b> NO DATA AVAILABLE
<b>TRADE NAME: GREEN-SEAL II</b> <b>MATERIAL USE: LUBRICATE &amp; SEAL PIPE THREADS (ENVIRONMENTALLY FRIENDLY)</b>	<b>SECTION 7 PREVENTION MEASURES</b>
<b>SECTION 2 HAZARDOUS INGREDIENTS</b>  APPROX. <u>COMPOSITION</u> <u>CONCENTRATION</u> <u>C.A.S.</u> <u>EXP.LIMITS</u> INGREDIENTS: NONE CONSIDERED HAZARDOUS	<b>GLOVES:</b> RUBBER OR CLOTH  <b>EYE PROTECTION:</b> GOGGLES RECOMMENDED  <b>VENTILATION:</b> LOCAL EXHAUST  <b>RESPIRATORY PROTECTION:</b> NONE REQUIRED  <b>LEAK &amp; SPILL PROCEDURE: (PRECAUTIONARY ONLY)</b> PREVENT MATERIAL FROM ENTERING WATERCOURSES BY CONTAINING WITH SAND OR EARTH.  <b>WASTE DISPOSAL:</b> DISPOSE IN COMPLIANCE WITH GOVERNMENT REGULATIONS AND LOCAL REQUIREMENTS.  <b>STORAGE REQUIREMENTS:</b> COOL, DRY AREA, AWAY FROM SOURCES OF HEAT.
<b>SECTION 3 CHEMICAL &amp; PHYSICAL PROPERTIES</b> <b>NAME: ENVIRONMENTALLY SAFE COMPOUND</b> PETROLEUM HYDROCARBON WITH ADDITIVES  <b>ODOUR:</b> MILD PETROLEUM  <b>COLOUR:</b> BLACK  <b>PHYSICAL STATE:</b> SEMI-SOLID  <b>SPECIFIC GRAVITY:</b> 1.077 g./c.c.  <b>BOILING POINT:</b> 260°C+ (500°F)  <b>SOLUBILITY:</b> NONE	<b>SECTION 8 FIRST AID MEASURES</b>  <b>SKIN:</b> WASH THOROUGHLY WITH SOAP AND WARM WATER  <b>EYE:</b> FLUSH WITH WATER FOR AT LEAST 15 MINUTES  <b>INHALATION:</b> VAPOUR PRESSURE IS NEGLIGIBLE. REMOVE VICTIM FROM FURTHER EXPOSURE  <b>INGESTION:</b> DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY.
<b>SECTION 4 FIRE &amp; EXPLOSION HAZARDS</b>  <b>PROCEDURES:</b> USE WATER ONLY AS A FOG. "FIRE FIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN POSITIVE PRESSURE DEMAND.  <b>UNUSUAL FIRE &amp; EXPLOSION HAZARDS:</b> NONE  <b>FLASH POINT:</b> GREATER THAN 171°C (340°F) ASTM D-92  <b>EXTINGUISHING AGENTS:</b> DRY CHEMICAL, WATERFOG, CO2, FOAM, SAND/EARTH	<b>SECTION 9 PREPARATION DATE</b>  PREPARED BY: ALAN S. HUEHN GENERAL MANAGER TOPCO OILSITE PRODUCTS LTD.  DATE: August 1, 2009  <b>PRODUCT NOT TDG REGULATED AS PER WHMIS STANDARD.</b>
<b>SECTION 5 REACTIVITY DATA</b>  <b>CHEMICAL STABILITY:</b> YES  <b>INCOMPATIBILITY:</b> STRONG OXIDIZING AGENTS  <b>HAZARDOUS DECOMPOSITION PRODUCTS:</b> CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF SULPHUR	
THE DATA PRESENTED HEREIN IS BELIEVED ACCURATE FOR THE SPECIFIC MATERIAL BUT IS IN NO WAY GUARANTEED. THE INFORMATION HEREIN MAY NOT BE APPLICABLE IF THE SPECIFIC MATERIAL IS USED IN COMBINATION WITH OTHER MATERIAL. TOPCO SALES ASSUMES NO RESPONSIBILITY AND MAKES NO WARRANTY IN CONNECTION WITH ANY USE FOR THE SPECIFIC MATERIAL. OTHER OR ADDITIONAL SAFETY MEASURES TO THOSE INDICATED MAY BE REQUIRED. THE USER, THEREFORE, ASSUMES FULL RESPONSIBILITY, BOTH AS TO PERSONS AND AS TO PROPERTY, FOR THE USE OF THESE MATERIALS.	