

Manufactured by



Setting a
HIGHERSTANDARD

CANADIAN MANUFACTURED WELL SERVICING TOOLS

Trico Heavy Lift Rod Elevator Capacity 50,000 (Lb)/25 Ton

The Trico Heavy Lift Rod Elevator is designed, tested, and documented to ensure compliance to API-8C specifications.

The Trico Heavy Lift product is manufactured by Topco Oilsite Products following a strict Quality Control program for overhead lifting equipment. This elevator is engineered to eliminate sharp edges or protrusions which could cause accidents or malfunctions during operation.

Description	Product Number
Elevator, Without Plates & Screws	553-575-500
COMPONENTS:	
1 Link	553-548-500
2 Lever, Rear	553-548-900
3 Spring	553-549-010
4 Lever, Release, Rear	553-551-000
5 Pin, Link	553-551-400
6 Latch, Release, Front	553-551-500
7 Spring Retaining Rings	553-551-800
8 Pin, Drive, Latch	553-766-100
ACCESSORIES:	
9 Screw (Allen Head), Plate	553-554-000A
Plates:	
10 5/8" - 3/4" Rods	553-550-000
11 3/4" - 7/8" Rods	553-550-200
12 1" Rod	553-550-700
13 1 1/4" Rod	553-550-800
OPTIONAL ELEVATORS AVAILABLE:	
14 1 1/8" Solid Body Steel Rod	553-575-100
15 1 1/4" Steel Rod Plate Type	553-575-200
16 1 1/4" Polish Rod Solid Body	553-575-300
17 1 1/2" Polish Rod Solid Body	553-575-800
18 Kit Repair (For Two Elevators)	553-579-600
19 Kit Repair for Polish Rods (For One Elevator)	553-579-300



Heavy Lift Plate Style



Heavy Lift Polish Rod Style

- LOW TEMP**
Suitable for low temperature service of -50° F.
- PROOF TESTED**
Proof tested to 1.5x the maximum rated load.

Combination Tap & Die Set

The Trico Combination Tap and Die Set is a handy on-the-spot thread chaser for use on all well servicing units. It allows the operator to repair rod threads and couplings in the field by setting correct factory thread pitch and contact area. The tool comes in three models and is made of the highest quality hardened steel to withstand severe service.



Description	Product Number
(Two Taps and Two Dies)	
1 5/8" and 3/4" API	556-786-010
2 3/4" and 7/8" API	556-786-020
3 7/8" and 1" API	556-786-030

Paraffin Knife

The Trico Paraffin knife features a field proven paraffin removing design. It is a rugged, flexible tool available in two sizes.

Description	Product Number
ACCESSORIES:	
1 Disk, Scraper, Paraffin Knife	556-792-800
2 2" (2 3/8" tubing)	556-793-000
3 Disk, Scraper, Paraffin Knife	556-792-900
4 2" (2 7/8" tubing)	556-792-700



Super Lift Snap-In Short Rod Hook Capacity 50,000 (Lb)/25 Ton

Trico rod hooks are designed for operating speed and safety. They feature a special snap-in latch mechanism which permits the elevator bail to enter the hook opening without the latch being released by the operator. When the bail is engaged the hook spring automatically forces the latch to a locked position, holding the elevator secure until released. The latch spring is enclosed in a housing to prevent fouling. Trico rod hooks are made of high-grade steel, and heat treated for long life.

Description	Product Number
Short Hook, Complete	554-578-600
COMPONENTS:	
1 Bail	
2 Bearings, Roller, Heavy Duty	554-543-400
3 Body	
4 Cap, Grease	554-542-500
5 Spring Housing	554-544-800
6 Latch	554-544-400
7 Lever	554-544-200
8 Nut	554-542-901
9 Pin, Latch	554-543-105
10 Pin, Lever	554-543-100
11 Steel Ball	554-542-700
12 Gasket, Grease Cap	554-542-500G
13 Screw, Grease Cap	554-542-600
14 Spring, Latch	554-544-700
ACCESSORIES:	
15 Kit, Repair	554-579-000
16 RFID/Asset Tracker	



LOW TEMP

Suitable for low temperature service of -50° F.

PROOF TESTED

Proof tested to 1.5x the maximum rated load.

Super Lift Snap-In Long Rod Hook Capacity 35,000 (Lb)/17.5 Ton

The Trico Snap-In Spring Lift Rod Hook has an extra long shank containing a heavy coil spring which supports the section of rods being pulled. The spring protects the rod threads while the rods are being removed from the tubing. The additional weight of this hook assists in unspooling the line from the pulling unit.



Description	Product Number
Long Hook, Complete	554-578-800
COMPONENTS:	
1 Bail	
2 Bearings, Roller, Heavy Duty	554-543-400
3 Body	
4 Cap, Grease	554-542-500
5 Spring Housing	554-544-800
6 Latch	554-544-400
7 Lever	554-544-200
8 Nut	554-542-901
9 Pin, Latch	554-543-105
10 Pin, Lever	554-543-100
11 Steel Ball	554-542-700
12 Gasket, Grease Cap	554-542-500G
13 Screw, Grease Cap	554-542-600
14 Spring, Latch	554-544-700
15 Spring, Coil	554-543-700
16 Grease Fitting	554-578-700
ACCESSORIES:	
17 Kit, Repair	554-579-000
18 RFID/ Asset Tracker	

LOW TEMP

Suitable for low temperature service of -50° F.

PROOF TESTED

Proof tested to 1.5x the maximum rated load.

Rod Buster Sucker Rod Wrench

The Trico snap-action Rod Buster Sucker Rod Wrench is made of high-grade alloy steel, hardened to resist wear. This lightweight (6 lb.) rugged tool is excellent for manual makeup and breakout of sucker rod joints. It features a counterbalanced grip to reduce fatigue. The cross-section of the handle is oval which provides a natural resistance to the wrench spinning when gripped. The head is spring-loaded and a hardened steel bushing is provided between the wrench head and handle.

Description		Product Number		
Sucker Rod Wrench Assembly Part	Rod Coupling Square Size (inches)	Size Of Sucker Rod (inches)	Handle Length (inches)	Wrench Head Part #2
1 555-560-000	7/8"	5/8" SR	19"	555-560-100
2 555-560-050	1"	3/4 - 7/8" SR	19"	555-560-200
3 555-560-065EL	1 1/8"	7/8" EL SR	19"	555-560-250EL
4 555-560-075	1 5/16"	1 - 1 1/4" SR, 1 1/4" PR	19"	555-560-275
5 555-560-175	1 1/2"	1 1/8" SR, 1 1/2" SR, 1 1/4" FG	19"	555-560-285
COMPONENTS:				
6 Kit Repair (consists of 1 spring, 1 plunger, 1 rivet, and 1 bushing)				555-560-950



Rod Spinner Capacity 50,000 (Lb)/25 Ton

The Topco Rod Spinner is engineered as a safety device to handle the release of sucker rod energy when a Progressive Cavity Pump is unseated. It reduces the risk of personal injury as well as preventing surface equipment from being damaged. It has been designed for efficiency to quick connect to a Rod Clevis on most energy service rigs, flushbys and rod rigs. It has a load rating of 50,000 lb allowing the Rod Spinner to be used to pull on both sucker and polish rods.



Description	Product Number
1" PE Rod Spinner	557-501-600
COMPONENTS:	
1 Cap, Grease	554-542-500
2 Gasket, Grease Cap	554-542-500G
3 Nut	554-542-901
4 Bearing	554-543-400
5 Screw, Grease Cap	554-542-600

Tubing Spinner Capacity 50,000 (Lb)/25 Ton

The Topco Tubing spinner is designed to create a safe environment when unseating downhole pumps and progressive cavity pumps which might have a torque buildup. This will cause the Sucker Rods to unscrew or relieve the torque violently. The Topco Tubing Spinner reduces the chance of injury and equipment damage by safely relieving the kinetic energy in the rod/pump assemblies.



Description	Product Number
COMPONENTS:	
1 2 7/8" Tubing Spinner	558-501-500
2 3 1/2" Tubing Spinner	558-501-600

Reversible Type Sucker Rod Socket

The Trico Reversible Type Sucker Rod Socket is a combination slip socket for fishing sucker rods, polished rods and sucker rod couplings (except surface-hardened couplings). Each socket is fitted with a reversible slip unit which has reverse wickers in each end. The large ID end of the slips will catch two sizes of couplings, while the opposite end will catch two sizes of rods. Multiple slips are available to catch worn boxes and pins. **They will not catch rods.**

Description		
Socket, Complete	2"	2 1/2"
Outside Diameter	1 29/32"	2 5/16"
COMPONENTS:		
PRODUCT NUMBER:		
1 Bowl	552-521-000	552-522-200
2 Guide, Spring	552-705-000	552-705-100
3 Ring, Control	552-524-400	552-525-100
4 Slips, Reversible		
1 1/4" to 1 1/2" Couplings	552-520-500	
5/8" and 3/4" Rods		
1 1/2" to 1 5/8" Couplings		552-521-600
3/4" and 7/8" Rods		
5 Spring	552-521-200	552-522-300
6 Top (with 3/4" API pin)	552-520-900	552-522-000
ACCESSORIES:		
7 Slips, Multiple	552-520-600	552-521-800
8 *Slips, Polished Rod		
1 1/8" and 1 1/4"	552-521-300	552-522-400
1 1/4" and 1 1/2"		552-522-500
9 *Slips, Reversible		
1 1/2" to 1 5/8" Couplings	552-520-530	552-521-500
1 1/2" to 1 5/8" Couplings		552-521-700



Type B Combination Sleeve-type Sucker Rod Socket

The Trico Type B Sleeve-Type Sucker Rod Socket is used for fishing rod body breaks and sucker rod couplings. The socket has an upper bowl fitted with rod slips suitable for catching two sizes of rods, and a lower bowl fitted with a single end slip unit designed to engage and catch one size sucker rod coupling. All parts of the Type B socket are interchangeable with O'Bannon.



Description		
Socket, Complete	2"	2 1/2"
Outside Diameter	1 29/32"	2 11/32"
COMPONENTS:		
PRODUCT NUMBER:		
1 Bowl, Lower	552-829-110	552-831-509
2 Bowl, Upper	552-829-310	552-831-609
3 Ring, Control	552-529-200	552-525-100
4 *Slips, Rod		
5/8" and 3/4" Rods	552-827-800	
3/4" and 7/8" Rods		552-830-100
5 *Slip Unit, Single End		
1 5/8" Coupling	552-528-100	
1 3/16" Coupling		552-531-409
6 Spring, Lower	552-821-200	552-822-300
7 Spring, Upper	552-829-400	552-831-700
8 Top (with 3/4" API pin)	552-828-900	552-822-000
9 *Slips, Rod		
3/4" and 7/8" Rods	552-827-900	
7/8" and 1" Rods		552-830-200
10 *Slip Unit, Single End		
1 3/8" Coupling	552-528-510	
1 1/2" Coupling	552-528-500	
1 9/16" Coupling	552-528-120	
1 5/8" Coupling		552-831-903
2" Coupling		552-531-402

Combination Sleeve-type Sucker Rod Socket

The Trico Combination Sleeve-Type Sucker Rod Socket is used for fishing rod breaks and sucker rod couplings. The socket has an upper bowl fitted with rod slips suitable for catching two sizes of rods, and a lower bowl fitted with a single end slip unit designed to engage and catch one size sucker rod coupling.

Description		
Socket, Complete	2"	2 1/2"
Outside Diameter	1 29/32"	2 5/16"
COMPONENTS:		
PRODUCT NUMBER:		
1 Bowl, Lower	552-529-000	552-531-500
2 Bowl, Upper	552-529-300	552-531-600
3 Guide, Spring, Lower	552-705-000	
4 Guide, Spring, Upper	552-705-400	552-705-100
5 Ring, Control	552-529-200	552-525-100
6 *Slips, Rod		
5/8" and 3/4" Rods	552-527-800	
3/4" and 7/8" Rods		552-530-100
7 *Slip Unit, Single End		
1 5/8" Coupling	552-528-100	
1 13/16" Coupling		552-531-400
8 Spring, Lower	552-521-200	552-522-300
9 Spring, Upper	552-529-400	552-531-700
10 Top (with 3/4" API pin)	552-528-900	552-522-000
11 *Slips, Rod		
1/2" and 5/8" Rods	552-526-200	
5/8" and 3/4" Rods		552-530-000
3/4" and 7/8" Rods	552-527-900	
7/8" and 1" Rods		552-530-200
12 *Slip Unit, Single End		
1 3/8" Coupling	552-528-510	
1 1/2" Coupling		552-531-410
1 9/16" Coupling	552-528-120	
1 5/8" Coupling		552-531-300
1 11/16" Coupling		552-531-310



Little Giant Sucker Rod Socket

The Trico Little Giant Sucker Rod is a combination slip socket used for fishing sucker rod breaks inside tubing. It can also be used inside a working barrel with corresponding size tubing and as a rod splicer for 2 inch tubing.



Description	Product Number
Socket, Complete	2"
Outside Diameter	1 11/16"
COMPONENTS:	
1 Bowl	552-527-000
2 Guide, Spring	552-705-400
3 Ring, Control	552-529-200
4 * Slips, Rod	
5/8" and 3/4" Rods	552-527-800
5 Spring	552-529-400
6 Top (with 5/8" API pin)	552-528-800
7 Slips, Rod	
1/2" and 5/8" Rods	552-526-200
3/4" and 7/8" Rods	552-527-900
8 Top (with 3/4" API pin)	552-528-900



TRUSTED

TESTED



TOPCO OILSITE PRODUCTS LTD.

Canada Location | 9519-28th NW Avenue | Edmonton, Alberta, Canada T6N 1N1

P: 780-436-3400 | F: 780-436-3659 | Toll Free: 1-800-222-6448 | Toll Free Fax: 1-888-867-2626